

6x3 Vac Assist

Diesel-Driven Centrifugal Pump Trailer Package
100-1063

Pump Specifications

Make Pioneer Model PP63C17 6" x 3" (150 mm x 76 mm) Size Impeller Diameter 17" (432 mm) Impeller Type **Enclosed** Max Flow 1,090 gpm (248 m³/h) 460 feet (140 meters) Max Head Max. Operating Speed 2,400 rpm 200 °F (93 °C) Max. Operating Temp. Max. Operating Press. 260 psi (1,800 kPa) Maximum Solid Size 0.75 inch (19 mm)

Engine Specifications

John Deere 4045HFC06 FT4 Engine Type Displacement 275 cu. in. (4.5 l) Fuel Consumption 7.03 gph (26.6 l/h) @ 1,800 rpm Continuous HP 142 hp (106 kW) 173 hp (126 kW) **Peak Intermittent HP Rating** FT4 Specifics (Def or No Def, DOC, SCR, etc.) DOC Safety Shut-Down Low oil pressure, high temp., v-belt failure Switches Oil pressure & temp gauge, ampmeter, Instrument Panel hourmeter, tachometer

Priming System

Priming System

Air Removal Cap.

Priming Chamber

Discharge Check
Valve

Mechanically driven
diaphragm-style vacuum pump
50 cfm (.02 cms)

Positive sealing air separation
w/stainless steel components

Swing style; ductile iron w/nitrile disc
Oil-lubricated mech seal allows pump
to run completely dry without damage



Features & Benefits

Indefinite run-dry capability
Extreme flow technology
Environmentally safe priming system
Auto-start controls
Skid options available

Package Specifications

Control Panel

Operating Speed (Min/Max)
Weight (Dry/Wet)
Instrument Compatibility

Trailer Brakes
Optional Adders

Fuel Capacity

135 U.S. gallons Controls Inc CX -Programmable Panel 1,200 / 2,400 rpm 5,690 / 6,649 lbs High/low level floats, transducers Electric

NTE automation

Materials of Construction

Impeller
Shaft
Wear Ring
Suction Cover
Volute
Brac-Plate/Bracket
Mechanical Seal

CA6NM Stainless Steel
17-4 PH Stainless Steel
ASTM A48 Class 40 Gray Iron
Ductile Iron ASTM A536 65-45-12
Ductile Iron ASTM A536 65-45-12
Ductile Iron ASTM A536 65-45-12
Silicon Carbide rotating and
Tungsten Carbide stationary

NTERENTS.COM

SALES@NTERENTS.COM


888,213,7950




6x3 Vac Assist

Diesel-Driven Centrifugal Pump Trailer Package 100-1063

Mechanical Dimensions



Performance Curve



NTERENTS.COM

SALES@NTERENTS.COM

888.213.7950